GHS SAFETY DATA SHEET

Date Revised: 1/16/15 Supersedes: New

Preformed Thermoplastic Alkyd Formulation (All Colors)

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Preformed Thermoplastic Alkyd Formulation (All Colors)

PRODUCT USE: Thermoplastic Road Marking Compound

EMERGENCY: 1-800-535-5053

SECTION 2 - HAZARDS IDENTIFICATION

GHS CLASSIFICATION:

Preformed Thermoplastic is not considered to be hazardous by the EPA under 29 CFR 1910.1200.

GHS LABEL: NOT REQUIRED

SIGNAL WORD: WARNING

Hazard Statements

Loose particles may cause irritation to the eyes.

May cause irritation by the inhalation of loose particles.

Contact with material in a molten form can cause serious burns.

Precautionary Statements

Overexposure may cause temporary respiratory irritation. Avoid breathing fume/gas/vapours while heating.

Use personal protective equipment as required



SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Concentration
Calcium Carbonate	471-34-1	30-50%
Glass Oxide; Glass (Not Applicable for Black)	65997-17-3	30-50%
Maleic Modified Glycerol Rosin Ester	94581-16-4	10-25%
Titanium Dioxide	13463-67-7	8-12%
Rosin Ester	8050-26-8	1-9%
Paraffinic Wax	8002-74-2	1-5%
EVA	24937-78-8	1-5%
Oil	Proprietary	1-5%

SECTION 4 - FIRST AID MEASURES

Contact with eyes: Remove contact lenses, if present and easy to do. Continue rinsing, irrigate copiously

with clean, fresh water for at least 10 minutes, holding eyelids apart.

Do not rub affected area.

Skin contact: Wash hands after handling and before eating. If skin irritation or rash occurs; get medical

advice/attention.

When exposed to molten or heated thermoplastic material, flush with cold water, do not

attempt to remove product from the skin, seek medical attention if necessary.

Inhalation: If existing respiratory/conditions are aggravated in your use of this product, get to well

ventilated area. If conditions persist seek medical advice/attention.

Ingestion: Rinse mouth with water (only if the person is conscious).

SECTION 5 - FIREFIGHTING MEASURES

Suitable Extinguishing Media: Water, CO2, Foam, Dry Chemical **Unsuitable Extinguishing Media:** Strong oxidizing agents

Exposure Hazards: Carbon Monoxide

Combustion Products: None

Protection for Firefighters: Wear self contained breathing apparatus in the positive mode to avoid smoke and fumes.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions: NONE for product at ambient temperature. Hot or molten thermoplastic may cause serious burns to

unprotected skin.

Environmental precautions: None

Methods for Clean up: Allow material to solidify if molten. Collect material or scrape off surface.

Materials NOT to be used for Clean up: Strong oxidizing agents

SECTION 7 - HANDLING AND STORAGE

Handling: Avoid the release and swirl of particles.

Wash hands after use. Do NOT eat, drink, or smoke in work areas.

Storage: Do NOT store at temperatures above 120*F.

Store in a cool, dry place.

SECTION 8 - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

Engineering Controls: Use in a well ventilated area.

Avoid the release and swirl of particles.

Wash hands after use. Do NOT eat, drink, or smoke in work areas.

PERSONAL PROTECTIVE EQUIPMENT (PPE):











Eye Protection: Face Shield / Safety glasses or goggles when molten

Skin Protection: Wear heat protective gloves when molten.

Wear long sleeve shirts, long pants, hard soled shoes.

Respiratory Protection: Provide adequate ventilation.

Use NIOSH/OSHA approved respiratory protection equipment in poorly ventilated areas.

Odor Threshold: N/A

Evaporation Rate: N/A

Vapor Pressure: N/A

Vapor Density: N/A

Boiling Range: N/A

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Ribbon/Sheeting

Odor: Alkyd Oil pH: N/A Melting Point: 200*F (93*C) minimum

Boiling Point: N/A
Flash Point: >475*F
Specific Gravity: 2.3 max
Solubility: Negligible

Auto-ignition Temperature: N/A VOC Content: HAPS Free

SECTION 10 - STABILITY AND REACTIVITY

Stability: stable at <475*F

Hazardous decomposition products: Carbon Monoxide, Carbon Dioxide

Conditions to avoid: Temperatures above 500*F

Incompatible Materials: Should not be brought into contact with strong oxidizing agents.

SECTION 11 - TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Inhalation, Ingestion, Eye Contact

Acute symptoms and effects: Shall NOT be classified as acutely toxic

Inhalation: Overexposure may cause temporary respiratory irritation.

Eye Contact: Particulates may cause irritation to the eyes. **Skin Contact:** Shall NOT be classified as a skin sensitizer.

Ingestion: Shall NOT be classified as a specific target organ toxicant (STOT)

Chronic (long-term) effects: This mixture does NOT meet the criteria for classification

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: Not classified as hazardous to the aquatic environment.

Mobility: Data not available

Degradability: Data not available

Bioaccumulation: Data not available

SECTION 13 - WASTE DISPOSAL CONSIDERATIONS

Follow local and national regulations. Consult disposal expert.

SECTION 14 - TRANSPORT INFORMATION

Proper Shipping Name: NOT relevant

Hazard Class: NOT relevant
Secondary Risk: NOT relevant
Identification Number: NOT relevant
Packing Group: NOT relevant
Label Required: NOT relevant

Marine Pollutant: None (non-environmentally hazardous)

SECTION 15 - REGULATORY INFORMATION

Precautionary Label Information: See section 2

Ingredient Listings: See section 3

Symbols: See section 8
Risk Phrases: See section 2
Safety Phrases: See section 2

SECTION 16 - OTHER INFORMATION

New Issue

Intended Use of Product: Road Markings

Disclaimer: This information is based upon the present state of our knowledge. This SDS has been compiled

and is solely intended for this product.