



### LIGHTWEIGHT - IDEAL FOR SMALLER MARKER JOBS

- 65 lb. (30kg) capacity
- All steel kettle
- One discharge valve on right side
- 25,000 BTU burner system controlled by a needle valve (optional thermostat control available)
- Lightweight - 90 lbs. (40kg)
- Optional second discharge valve available
- Optional marker storage basket

The Model 50150 is an economical solution for marker application and/or crack fill. At just under 90 lbs., The 50150 is very portable and easy to maneuver. Unit rides on two solid rubber tires on the front and two swivel casters on rear.

The RBM300 is a fully equipped bituminous applicator capable of switching from a walk-behind unit to a self-propelled unit in moments. The RBM300 with the optional Graco LineDriver is the only one man operation, auto-propelled bitumen applicator, and still portable enough to be transported on a regular pick-up truck

The unit comes standard with an automatic thermostat system, material thermometer and external hand torch for burner lighting and discharge valve heating. A storage basket is located within easy reach of the operator and provides ample space for markers or bitumen.

The RBM300 delivers fast start-up time, high capacity and maneuverability, providing a safe and efficient method for road marker application.

### HEAVY DUTY - FOR HIGH PRODUCTION

- 300 lb. (159kg) capacity
- All steel kettle
- Two discharge valves
- 60,000 BTU burner system controlled by an automatic thermostat complete with pilot safety valve
- Marker storage basket
- Foot brake
- Weight: 250 lbs (113 kg)



Trantex, Inc. • Houston, TX.  
281-448-7711  
Email: [sales@TrantexInc.com](mailto:sales@TrantexInc.com)  
[www.TrantexInc.com](http://www.TrantexInc.com)

Centerline • Grand Prairie, TX.  
972-647-8300  
Email: [sales@CLSUSA.com](mailto:sales@CLSUSA.com)  
[www.CLSUSA.com](http://www.CLSUSA.com)

FL. Transcor, Inc. • Jacksonville, FL.  
904-783-3302  
Email: [sales@FLTranscor.com](mailto:sales@FLTranscor.com)  
[www.FLTranscor.com](http://www.FLTranscor.com)