

Material Safety Data Sheet

24 Hour Emergency: CHEMTREC: 1-800-424-9300

Outside U.S. and Canada Chemtrec: 703-527-3887 NOTE: CHEMTREC, CANUTEC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals

Section 1 - Chemical Product / Company Information

Product Name:	YELLOW CHLORINATED RUBBER ZONE MARKING PAINT	Revision Date:	02/13/2012
Identification Number:	12Y-D243	Supercedes :	10/29/2010
Product Use/Class:	55		
Supplier:	Centerline 530 Jesse St., Grand Prairie, TX 75051		
Phone:	972-647-8300		

Section 2 - Composition / Information On Ingredients

a					
Chemical Name	CAS No.	<u>Wt. %</u>	ACGIH TLV-TWA	ACGIH TLV-STEL	<u>OSHA PEL-TWA</u>
TOLUENE	108-88-3	16.	50	150	100
ALIPHATIC PETROLEUM DISTILLATES	64742-89-8	7.	300	400	300

Section 3 - Hazards Identification

Emergency Overview: Flammable liquid and vapor.

Effects Of Overexposure - Eye Contact: Mild eye irritation. Direct eye contact may cause irritation.

Effects Of Overexposure - Skin Contact: Direct skin contact may cause irritation. Skin irritant.

Effects Of Overexposure - Inhalation: Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

Effects Of Overexposure - Ingestion: Harmful: may cause lung damage if swallowed.

Effects Of Overexposure - Chronic Hazards: Chronic exposure may cause nausea and vomiting, higher exposure causes unconsciousness.

Primary Route(s) Of Entry: Skin Contact, Inhalation, Ingestion, Eye Contact

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Section 4 - First Aid Measures

First Aid - Eye Contact: Flush eye(s) immediately with plenty of water. Rinse with plenty of water.

First Aid - Skin Contact: Wash off with soap and water.

First Aid - Inhalation: Move to fresh air.

First Aid - Ingestion: If swallowed seek medical attention. Call a physician or Poison Control Center immediately.

Section 5 - Fire Fighting Measures

Flash Point, F: 45 Deg.

Extinguishing Media: Carbon Dioxide, Dry Chemical, Foam

Unusual Fire And Explosion Hazards: Remove all sources of ignition. May be ignited by open flame. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Vapors are heavier than air and may spread along floors.

Special Firefighting Procedures: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Chemical Name	LEL	UEL	<u>Flash point f.</u> <u>Deg</u>	AUTO-IGNITION TEMP. F DEG
TOLUENE	1.00	7.00	45	896.00
ALIPHATIC PETROLEUM DISTILLATES	0.90	7.00	50	450.00

Section 6 – Accidental Release Measures

Steps To Be Taken If Material Is Released Or Spilled: Soak up with inert absorbent material and dispose of as hazardous waste.

Section 7 - Handling And Storage

Handling: Containers of this material may be hazardous when emptied. Hazardous fumes can also occur in post-processing operations. Handle in accordance with good industrial hygiene and safety practice. All metal parts of the mixing and processing equipment must be grounded.

Storage: Harmful - Store away from foodstuffs.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls: Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits. Ensure adequate ventilation.

Respiratory Protection: In the case of respirable dust and/or fumes, use self-contained breathing apparatus. In case of insufficient ventilation, wear suitable respiratory equipment.

Skin Protection: Impervious gloves.

Eye Protection: Safety glasses with side-shields.

Other protective equipment: Impervious clothing.

Hygienic Practices: It is good practice in industrial hygiene to avoid contact with solvents by using appropriate protective measures whenever possible.

Keep away from children.

Section 9 - Physical And Chemical Properties

Odor:

Characteristic

12Y-D243

Appearance:	Heavy Yellow Liquid
Specific Gravity:	1.584
Physical State:	Liquid

(See section 16 for abbreviation legend)

CHEMICAL NAME	VAPOR DENSITY	EVAPORATION RATE	BOILING POINT	<u>VP mmHg</u>	<u>at DEG. F</u>
TOLUENE	3.20	2.00	233	16.70	77
ALIPHATIC PETROLEUM DISTILLATES	3.80	2.00	240	10.20	68

Section 10 - Stability And Reactivity

Conditions To Avoid: Avoid heat, sparks, open flame and other ignition sources.

Incompatibility: Keep away from strong oxidizing agents, heat and open flames.

Hazardous Decomposition Products: Incomplete combustion may produce carbon monoxide and other toxic gases.

Hazardous Polymerization: Will not occur.

Stability: Stable under normal conditions.

Section 11 - Toxicological Information

No Data.

Section 12 - Ecological Information

Ecological Information: Do not allow material to contaminate ground water system.

Section 13 - Disposal Information

Disposal Information: Contact waste disposal services. Do not flush into surface water or sanitary sewer system. Dispose of according to local regulations.

Section 14 - Transportation Information

DOT Proper Shipping Name:Paint, Flammable LiquidDOT Hazard Class:3DOT UN/NA Number:1263

Packing Group: Resp. Guide Page: II 128

Section 15 - Regulatory Information

CERCLA – SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

SARA Section 312:

<u>Chemical Name</u> TOLUENE ALIPHATIC PETROLEUM DISTILLATES

SARA Section 313:

CAS Number 108-88-3 64742-89-8

12Y-D243

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name

TOLUENE

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

None

U.S. State Regulations: As follows -

California Proposition 65:

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

None

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

Chemical Name TOLUENE

International Regulations: As follows -

CANADIAN WHMIS:

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

CANADIAN WHMIS CLASS:

HMIS Ratings:

Health: 2

Flammability: 3

Reactivity: 0

VOLATILE ORGANIC COMPOUNDS, GR/LTR: 365.86

REASON FOR REVISION:

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.

file:///Pl/MSDS/Publish/12Y-D243.HTM[1/16/2013 8:11:44 AM]

CAS Number 108-88-3

CAS Number 108-88-3